

| Model Name | | Unit | ARNU24GTYA4 | ARNU36GTYA4 | ARNU48GTYA4 |
|---|--|-------------------------|--|-----------------------|-----------------------|
| Power Supply | - | V, Φ , Hz | 220-230-240, 1, 50/60 | 220-230-240, 1, 50/60 | 220-230-240, 1, 50/60 |
| | Running Current by | A | 0.47 - 0.45 - 0.43 | 0.67 - 0.64 - 0.61 | 0.99 - 0.95 - 0.91 |
| Cooling Capacity | Rated | kW | 7.1 | 10.6 | 14.1 |
| | | kcal/h | 6,100 | 9,100 | 12,100 |
| | | Btu/h | 24,200 | 36,200 | 48,100 |
| Heating Capacity | Rated | kW | 8.0 | 11.9 | 15.9 |
| | | kcal/h | 6,900 | 10,200 | 13,200 |
| | | Btu/h | 27,300 | 40,600 | 54,200 |
| Power Input | H/M/L | W | 44 / 36 / 29 | 63 / 47 / 36 | 98 / 70 / 44 |
| Running Current | H/M/L | A | 0.47 / 0.40 / 0.32 | 0.67 / 0.52 / 0.40 | 0.99 / 0.74 / 0.47 |
| Fan | Type | - | 3D Turbo Fan | 3D Turbo Fan | 3D Turbo Fan |
| | Air Flow Rate(H/M/L) | ms/min | 22 / 21 / 19 | 27 / 24 / 21 | 32 / 28 / 23 |
| Fan Motor | Type | - | Brushless DC | Brushless DC | Brushless DC |
| | Drive | - | Direct | Direct | Direct |
| | Output | W x No. | 157 x 1 | 157 x 1 | 157 x 1 |
| | FLA(Full Load Ampere) | A | 1.97 | 1.97 | 1.97 |
| Heat Exchanger | (Rows x Columns x FPI) x No. | - | (3 x 12 x 21) x 1 | (3 x 12 x 21) x 1 | (3 x 12 x 21) x 1 |
| | Face Area | m ² | 0.5 | 0.5 | 0.5 |
| Dimensions | Net(W x H x D) | mm | 1,050 x 330 x 1,050 | 1,050 x 330 x 1,050 | 1,050 x 330 x 1,050 |
| | Shipping(W x H x D) | mm | 1,137 x 395 x 1,132 | 1,137 x 395 x 1,132 | 1,137 x 395 x 1,132 |
| Weight | Net | kg | 30.0 | 30.0 | 30.0 |
| | Shipping | kg | 37.9 | 37.9 | 37.9 |
| Exterior | Color | - | White | White | White |
| | RAL Code | - | RAL 9003 | RAL 9003 | RAL 9003 |
| Air Filter | Type | - | Long life | Long life | Long life |
| Temperature Control | | - | Microprocessor, Thermostat for cooling and heating | | |
| Sound Absorbing / Thermal Insulation Material | | - | Foamed polystyrene | | |
| Safety Device | | - | Fuse | Fuse | Fuse |
| Refrigerant | Type | - | R410A/R32 | R410A/R32 | R410A/R32 |
| | Additional Charging Amount (CF Value of IDU) | kg(each) | 0.49/0.41 | 0.49/0.41 | 0.49/0.41 |
| | Control Type | - | EEV | EEV | EEV |
| Drain Pipe | O.D / I.D | mm(inch) | 32 / 25 | 32 / 25 | 32 / 25 |
| Piping Connection | Liquid | mm(inch) | Φ 9.52 (3/8) | Φ 9.52 (3/8) | Φ 9.52 (3/8) |
| | Gas | mm(inch) | Φ 15.88 (5/8) | Φ 15.88 (5/8) | Φ 15.88 (5/8) |
| | Connection Type(Liquid) | - | Flare | Flare | Flare |
| | Connection Type(Gas) | - | Flare | Flare | Flare |
| Sound Pressure Level (H / M / L) | | dB(A) | 39 / 37 / 34 | 43 / 39 / 37 | 47 / 44 / 39 |
| Sound Power Level (H / M / L) | | dB(A) | 48 / 46 / 43 | 52 / 48 / 46 | 56 / 53 / 48 |
| Connecting Cable | Communication Cable (VCTF-SB) | mm ² x cores | 1.0~1.5 x 2C | 1.0~1.5 x 2C | 1.0~1.5 x 2C |

Note