

-GENESIS-

Riser Rated Security & Control Cable

Part Number: 2228

18 AWG 3 Stranded Conductors Shielded

Ratings CMR, CL3R, FPLR, FT4, Sunlight Resistant

Approvals ETL Listed

Construction

Conductor 18 AWG 19 Strand Bare Copper

Conductor Count 3

Insulation Polypropylene (0.006" nom.)

Insulation Colors Black, Red, White

Lay Length 3.25" nom.

Shielding Aluminum Foil/Mylar w/ 24 AWG Tinned-Copper Drain

Rip Cord Yes

Jacket PVC (0.015" nom.)

Overall Diameter 0.161" nom.

Print Legend GENESIS P/N 2228 3C18 SHIELDED 3038058 (ETL) CL3R OR FPLR OR CMR C(ETL)US FT4
SUN RES 75C (RoHS) W/O #XXXXXX-XXXXXX XXXX FT DEVICE/ZONE A B C D E F 1 2 3
4 5 6 7 8 9

Properties

Operating Voltage 300 Volts max.

DC Resistance 6.66 Ohms/1000' at 20°C

Capacitance 36.3 pF/ft. nom.

Impedance 41 Ohms nom.

Temperature -20°C to 75 °C

Flame Rating UL 1666 (Riser); CSA C22.2 No. 2556 (FT4)

RoHS Compliant Yes

Country of Origin USA